

820

Single jet meter
Semi dry protected register
Any position Class C



Main characteristics

DN 15 to 20 PN16

Semi dry protected register

Class C any position

High resistance to foreign bodies

Large measuring range

Small pressure loss

Noiseless operation

Can be retro-fitted with the HRI pulser

Application

High accuracy metering of water containing solid particles is now possible, regardless of installation position

Due to its exclusive patented hydrodynamic balancing system, the 820 meter is the first velocity meter approved in class C for any position

The 820 meter is the perfect solution for ensuring accurate and reliable metering regardless of installation and operating conditions

Available options

HRI electronic sensor (Pulse Unit or Data Unit)

Pipe to meter couplings

Non-return valve

Upstream and downstream stop-valves

UK & Ireland Enquiries
Sensus Metering Systems
11 The Quadrangle, Abbey Park,
Romsey, Hampshire SO51 9DL UK
T: +44 (0) 1794 526100
F: +44 (0) 1794 526101
Email: info.gb@sensus.com

www.sensus.com

International Enquiries
Sensus Metering Systems GmbH Ludwigshafen
Industriestrasse 16,
67063 Ludwigshafen Germany
T: +49 (0) 621-6904-0
F: +49 (0) 621-6904-1409
Email: info.int@sensus.com

www.sensus.com

 **SENSUS**
METERING SYSTEMS